



MARYLAND PIPE & SUPPLY CO., LLC



PEX Brass Fittings

SUBMITTAL AND DATA SHEET

***NSF & UPC Approved *Can Be Used with Pex Tubing**

***Manufactured to ASTM Standard F1807**

***Manufactured to ASTM Standard F876-877**

SUBMITTAL INFORMATION

***Typical Applications:** Potable code & hot domestic water hydronic heating systems & radiant heating systems

***Use with:** Pex tubing in accordance with ASTM F876 & F877

***Material:** Forged No-Lead Brass

***Vibration:** Excellent resistance

***Complies with NSF/ANSI 61-2012**

***Adapter threads to ANSI B1.20.1, Adapter solder ends to ANSI B16.18. All CNC machined ends.**

***Pressure & Temperature:**

160 PSI @ 73°F

100 PSI @ 180°F

80 PSI @ 210°F

PEX Poly Alloy Fittings

Features & Benefits:

*Modified Polyphenylsulfone (PPSU)

*Molded from Acudel® Resin

*Lead Free Compliant

*Approvals: NSF 14, NSF/ANSI 61/Annex G; ASTM F2159, F877; CSA B137.5

*For use in Hot and Cold Potable Water Distribution Systems

*200°F Max Service Temperature

