



MARYLAND PIPE & SUPPLY CO., LLC



SDR 35 Gasketed

Specifications

SUBMITTAL AND DATA SHEET

SDR 35 Molded Gasketed Fittings:

*Injection molded 4" to 12", fabricated 15" to 48"

*Manufactured in accordance with ASTM D-3034, ASTM F-1336 and CSA B182.2.

*Injection molded from virgin PVC compound having a cell classification of 12454 or 13343 in accordance with, and certified by the NSF to meet ASTM D-1784.

*Gaskets manufactured in accordance with ASTM F-477 or ASTM F-913.

*Gasket joints comply with ASTM D-3212 Internal Pressure Test (ex-filtration) and Vacuum Test (infiltration) with gasketed joint misalignment and 5% top load deflection.

*Gaskets shall be firmly seated in fitting in order to ensure proper installation and to prevent dislocation or misalignment during system assembly.

*Third party tested, certified and listed by NSF to meet specifications defined in ASTM D3034, ASTM F1336 and CSA B182.2, where applicable

SDR 35 Gasketed Information

DO NOT USE FITTINGS FOR COMPRESSED AIR OR GASES.

DO NOT TEST PVC PIPING SYSTEMS WITH COMPRESSED AIR OR GASES.

DO NOT USE FITTINGS WITH LIQUIDS NOT RECOMMENDED BY MANUFACTURER.

MODIFICATION OF FITTINGS VOIDS THE WARRANTY.

SPECS SUBJECT TO CHANGE WITHOUT NOTICE.

NSF CERTIFIED

MANUFACTURERS: