

Operating Performance

Operating Weight	3,900 lb
Max. Bucket Breakout Force	4,250 lb
Max. Arm Digging Force	1,843 lb
Arm Length	3 ft 8.5 in
Slew Speed	9.2 rpm
Traction Force	4,361 lb
Ground Pressure	4.3 psi
Travel Speed – Low	1.4 mph
Travel Speed – High	2.6 mph

Hydraulic System

Total Hydraulic Flow	13.4 gpm
Auxiliary Hydraulic Flow	8.9 gpm
Hydraulic System Pressure	3,046 psi

Engine

Model/Made	Yanmar/3TNV74
Displacement	60.2 cu in
Horsepower @ 2,400 rpm	15 hp
Max. Torque @ 1,800 rpm	38.2 ft-lb

Fluid Capacities

Engine Lubrication	4.5 qt
Cooling System	4.0 qt
Fuel Tank Capacity	5.8 gal
Hydraulic Reservoir Capacity	4.2 gal

Machine Dimensions

Max Reach	13 ft 5.0 ft
Max Reach at Ground Level	13 ft 2.9 in
Max Digging Depth	7 ft 10.0 in
Max Vertical Digging Depth	6 ft 9.1 in
Max Dig Height	12 ft 3.2 in
Max Dumping Height	8 ft 10.5 in
Front Swing Radius	4 ft 10.3 in
Front Swing Radius with Boom Offset	3 ft 9.4 in
Tail Swing (Slew) Radius	3 ft 6.3 in
Transport Length	12 ft 8.3 in
Transport Height	7 ft 4.87 in
Ground Clearance	8.1 in
Undercarriage Length	4 ft 11.9 in
Track Width (Rubber)	9.0 in

Undercarriage Width – Track Retracted 38.6 in
Undercarriage Width – Track Extended 51.2 in